CLAIMS

What is claimed is:

1. (Original) A method of handling a group call in a CDMA wireless communications system, comprising:

classifying members of a group call into a first class or a second class, said first class comprising members authorized to both talk and listen, said second class comprising members authorized to listen but not to talk;

initially assigning a private downlink channel to each member of said group call belonging to said first class;

assigning a public downlink channel to at least one member of said group call belonging to said second class;

changing the classification of a first member of said group call belonging to said first class to be said second class in response to said member not talking for a predetermined time period during said group call; and

changing the downlink channel assignment of said first member from said respective private channel to said public downlink channel assigned to said at least one member of said group call belonging to said second class in response to said change in classification.

2. (Original) The method of claim 1 further comprising providing both private and public downlink channels simultaneously.

Ericsson Ref. No. P12620-US1 Application Serial No. 09/909,395

- 3. (Original) The method of claim 1 further comprising changing the downlink channel assignment in response to a request to speak from at least one member of said group call belonging to said second class.
- 4. (Original) The method of claim 1 further comprising staggering a change of status for pilot channels and traffic channels as members of said first group transition to members of said second group.
- 5. (Original) The method of claim 1 further comprising placing a member of said second group on said respective private channel just freed by said changing the downlink channel assignment of said first member from said respective private channel to said public downlink channel.

6. (Currently amended) A method of handling a group call in a CDMA wireless communications system, comprising:

classifying members of a group call into a first class or a second class, said first class comprising members authorized to both talk and listen, said second class comprising members authorized to listen but not to talk;

initially assigning a private downlink channel to each member of said group call belonging to said first class;

assigning a public downlink channel to at least one member of said group call belonging to said second class;

initially transmitting voice on a Reverse Traffic Channel and a pilot signal on a

Reverse Pilot Channel uplinking information on a first and a second control

channel, during said group call, by a first member of said group call belonging to
said first class; and

thereafter, ceasing transmission on the Reverse Traffic Channel the uplinking of information on said first control channel, during said group call, by a first member in response to said first member not talking for a first predetermined time period during said group call, while continuing to transmit the pilot signal on the Reverse Pilot Channel.

7. (Currently amended) The method of claim 6 further comprising:

thereafter, ceasing transmission of the pilot signal on the Reverse Pilot Channel
the uplinking of information on said second control channel, during said group

call, by said first member in response to said first member not talking for a second predetermined time period during said group call; and changing the downlink channel assignment of said first member from said respective private channel to said public downlink channel in response to said first member not talking for said second predetermined time period during said group call.

- 8. (Original) The method of claim 6 further comprising ending said group call when all of said members are silent for a length of time greater than a predetermined threshold.
- 9. (Original) The method of claim 6 further comprising processing, at said base station both private and public downlink channels concurrently.
- 10. (Original) The method of claim 6 further comprising allowing members of said second class to move to said first class and further assigning such moving members a private downlink channel on which to communicate.

11. (Original) A method of handling a group call in a CDMA wireless communications system, comprising:

classifying members of a group call into one of either a first class or a second class, said first class comprising members authorized to both talk and listen, said second class comprising members authorized to listen but not to talk;

initially assigning a private downlink channel and a private uplink channel to a first member of said group call belonging to said first class;

initially assigning the remaining members of said group call to one or more public downlink channels; and

thereafter, during said group call, substantially simultaneously:

reclassifying said first member to said second class;

reassigning said first member to said public downlink channel;

reclassifying a second member of said group call belonging to said second class to said first class;

reassigning said private downlink channel and said private uplink channel to said second member.

- 12. (Currently amended) A method of facilitating communication comprising: establishing a group of users in a CDMA wireless communication system, each of said users having a mobile terminal; initiating a call to at least one other user of the group from a first mobile terminal; assigning a first private downlink channel to said first mobile terminal; assigning other private downlink channels to mobile terminals associated with said at least one other user of the group as needed; and assigning a public downlink channel to remaining users of the group.
- 13. (Currently amended) The method of claim 12 further comprising timing out users such that private <u>downlink</u> channels are freed for other users within the group.
- 14. (Currently amended) The method of claim 12 further comprising allowing inactive users associated with the public <u>downlink</u> channel to secure a private <u>downlink</u> channel upon actuation of a command on their mobile terminal.
- 15. (Currently amended) The method of claim 12 further comprising limiting the other private <u>downlink</u> channels to a predetermined number.

16. (Original) A method of handling a group call in a CDMA wireless communications system, comprising:

dividing members of a group call to a first class or second class, said first class comprising members authorized to both talk and listen, said second class comprising members authorized to listen but not to talk;

assigning a private downlink/uplink channel pair to a member of said first class for communicating between said member of said first class and a base station;

assigning a public downlink channel without a corresponding uplink channel to a member of said second class for receiving downlink communications from said base station;

wherein, during a given group call, said first member and said second member receive downlink communications from said base station over their respective downlink channels.